



PondMate Pumps

Low Voltage Pumps

PLV Series

PLV Series

A low voltage, energy efficient pump with flow adjuster, the PLV Series is suitable for both fresh and marine water. Can be used in aquarium, water garden fountain and waterfall applications.



Advantages

- Durable construction
- Features flow control adjuster
- Energy efficient
- Optional in-line use
- Easy installation
- Comes with 5 metre cable
- Suitable for salt water applications
- Each unit individually wet-tested to guarantee reliable operation

Construction

- Wear-resistant ceramic shaft ensures long life
- More powerful and energy-efficient magnetic rotor
- Weatherproof transformer
- Thermal protector
- Encapsulated epoxy resin motor ensures safety, reliability and durability

**COMES WITH
LOW VOLTAGE
TRANSFORMER**



**TWO YEAR
WARRANTY**

“moving water”

| Model | Style | Power Consumption | Max Head | Max Flow | Total Head (m) | | | | | | Connection Size | Qty in Carton | |
|-----------|---|-------------------|----------|----------|-------------------|----|-----|----|-----|---|-----------------|---------------|----|
| | | | | | 0.5 | 1 | 1.5 | 2 | 2.5 | 3 | | | |
| 240V/50Hz | | (W) | (m) | (l/hr) | Capacity in l/min | | | | | | Outlet (mm) | | |
| PM350PLV |  | 6 | 0.70 | 350 | 3 | | | | | | | 13/13 | 18 |
| PM550PLV |  | 10 | 1.22 | 550 | 6 | 3 | | | | | | 13/19 | 16 |
| PM700PLV | | 10.5 | 1.20 | 610 | 10 | 4 | | | | | | 13/19 | 16 |
| PM1000PLV |  | 17 | 2.00 | 1100 | 11 | 8 | 6 | | | | | 13/19 | 12 |
| PM1500PLV | | 20 | 2.00 | 1500 | 18 | 13 | 6 | | | | | 13/19 | 12 |
| PM2400PLV | | 40 | 2.40 | 2300 | 33 | 28 | 18 | 11 | | | | 13/19 | 8 |
| PM3500PLV | | 70 | 2.75 | 4000 | 50 | 41 | 33 | 21 | 11 | | | 19/25 | 4 |

Additions to the PLV Series:

- 10 metre low voltage extension cable (30 per carton)
- 13mm adaptor to suit PM350PLV & PM550PLV

PMEXTCABLE
PMADAPTOR

