

Pressure Tanks

A wide range of tanks



KEY FEATURES

- Tank capacities up to 450 litres covering a wide range of applications
- Standard range up to 690 kPa, with high-pressure model up to 1100 kPa
- High quality steel construction provides durability
- Five-year warranty ensures peace of mind

TANKS

A robust metal shell with a butyl rubber diaphragm and polypropylene liner ensures a long life.



PT

Model	Capacity litres	Max Working Pressure kPa/psi	Mounting Type	Inlet Size BSP	Pressure Switch Setting kPa/psi		
					140-280 20-40	210-350 30-50	280-420 40-60
					Nominal Draw-off Litres		
PT08	8	690/100	Pipe	1" Male	2.9	2.4	2.1
PT18	18	690/100	Pipe	1" Male	4.8	5.5	4.8
PT53	53	690/100	Foot	1" Female	19.3	16.3	14.1
PT75	75	690/100	Foot	1" Female	27.3	23.1	20.0
PT75HP	75	1100/160	Foot	1" Female	27.3	23.1	20
PT121	121	690/100	Foot	1" Female	44.1	37.8	32.3
PT167	167	860/125	Foot	1 1/4" Female	60.9	52.2	44.6
PT234	234	860/125	Foot	1 1/4" Female	85.4	73.2	62.4
PT325	325	860/125	Foot	1 1/4" Female	118.6	101.7	86.7
PT450	450	860/125	Foot	1 1/4" Female	164	140.8	120.1