

**APPLICATIONS**

Water supply for house and garden.  
Ideal for household water supply, the Grundfos CH-PC Minimises annoying shower temperature fluctuations.

**FEATURES**



- CH-PC incorporates dry run protection
- Quiet operation
- Vital parts made of stainless steel for a long life
- Built-in thermal protection (1 x 240V)
- Electrophoresis coating to resist corrosion

**CONSTRUCTION**

- Stainless steel impellers, intermediate chambers and shaft
- Carbon / ceramic seal
- IP54 motor
- Insulation Class F
- Maximum ambient temperature: +55°C

**PERFORMANCE**

Pumps	Discharge Pressure (kPa/psi)						
	150	200	250	300	350	400	450
	22	29	36	44	51	58	65
	Output (l/min)						
CH2-30 PC15	49	35	20	-	-	-	-
CH2-40 PC15	54	49	40	27	16	-	-
CH2-50 PC15	54	49	46	37	30	21	-
CH2-60 PC22	57	53	48	44	37	30	24
CH4-40 PC15	83	72	54	26	-	-	-
CH4-50 PC22	103	95	83	66	44	17	-
CH4-60 PC22	111	103	95	81	72	60	46
CH2-30 PT8	31	24	13	-	-	-	-
CH2-40 PT18	54	49	40	26	8	-	-
CH2-50 PT18	57	53	46	34	28	-	-
CH2-60 PT18	58	56	50	45	36	29	23
CH4-40 PT18	106	86	64	-	-	-	-
CH4-50 PT18	120	108	89	68	45	19	-
CH4-60 PT18	127	121	109	98	83	69	49

As a guide 1 tap  = 10 litres per minute • 1 sprinkler  = 15 litres per minute



CH-PC



CH-PT

