

## Mission Statement



To manufacture rainwater tanks, uniquely suitable for the storage of fresh drinking water.

Tanks which outlast and outperform any other tanks on the market which are built for this purpose. And last but not the least, tanks with a minimal environmental impact.

Stainless steel is as familiar and robust as the kitchen sink. It is widely acknowledged as being unsurpassed for strength, durability and hygiene.

The traditional construction of ordinary, corrugated steel rainwater tanks in Australia involves drilling or punching numerous holes to fix the corrugated sheets with rivets or screws. This is also the weakest link in the tank. Each one of these rivets or screws requires sealing, and each has the potential to be the source of corrosion, and leakage.

To overcome this problem *Stainless Rainwater Tanks* pioneered and developed a unique method of spot welding the stainless steel corrugated sheets, and now offers a premium product at a competitive price. *Stainless Rainwater Tanks* manufactures an extensive range of reliable, durable, safe and hygienic stainless steel rainwater tanks, with none of the disadvantages of other rainwater tanks.

**"When hygiene and durability are paramount, there is no alternative to Stainless Steel"**

### Standard Tank Range

All tanks have a twenty-five (25) year warranty, and are fitted with a screened strainer, mosquito-proof overflow, and a 1" (25mm) outlet.

### Round Tanks

Gallons	Litres	Diameter	Height
660	3000	1600	1570
1100	5000	2050	1570
1600	7400	2000	2350
Squat 2300	10200	2900	1570
3350	15100	3500	1570
4000	18000	3500	1880
5000	22600	3500	2350
Squat 5100	23000	4000	1880
6400	30000	3500	3100
8650	39000	4000	3100

## Slim Line Series

### Super Slim

Litres	Length	Width	Height
3000	3000	680	1570
5000	4800	680	1570

### Slim Lines

Litres	Length	Width	Height
3300	2600	880	1570
5100	3900	880	1570

### Jumbo Slim

Litres	Length	Width	Height
5100	3000	1200	1570
7000	4000	1200	1570

- Please inquire for other sizes as tanks are available in diameters from 1200mm to 4000mm and height increment of 800mm, 1230mm, 1570mm, 1880mm, 2350mm, 2660mm, 3100mm. Slim line tanks are limited to a height of 1570mm.
- Delivery charge may apply.
- Tanks over 23000 L (5100gal) require a crane to install.
- Optional extras for our tanks include level gauges, oversized and multiple overflows, screwed inspection lids, oversized inlet strainers, inlet filters, multiple outlets ranging in size up to 150mm (6 inches), high outlets for bucket taps and stainless steel poles.